

ANALYSIS OF THE TRASH FROM THE CLEANING OF SEED COTTON

Kodirova Feruza

Namangan Institute of Civil Engineering, Uzbekistan

Sarimsakov Olimjon

Namangan Institute of Textile Industry

E-mail: olimjon5008@mail.ru

Annotation. The article talks about a dynamic model that explains how impurities travel inside the bulk of cotton and how they are elastically connected to the cotton. Based on the parameters of the cleaning drum, patterns have been observed in the movement of the particles inside and on the surface of the cotton mass as a result of forces acting on them. The radius of the cleaning drum and the angular velocity of the drum represent the forces acting on the particle.

Keywords: fibers, spiked cylinder, friction force, screen bars, angular velocity.

Known designs of cleaners are based on shock-shaking action on fibrous material [1]. Even though the improvement of purifier designs is an ever-increasing trend, the industry's demand for highly efficient purifiers is not decreasing. It should also be noted that with the improvement of purifier designs, their main working elements remain the same. This, in our opinion, is a consequence of the fact that the essence of the process of cleaning fibrous material from impurities is not sufficiently disclosed; the existing dynamic and mathematical models do not fully correspond to the real cleaning situation. Therefore, any progressive attempts to describe the purification process using the latest scientific advances should be welcomed.

Linear [2], and nonlinear [3] dynamic models of the process of cleaning fibrous material are known. Models have also been developed aimed at separating impurities from the surface of a layer of fibrous material [4], separating debris from fibrous material when layers are shifted [5], and separating debris during their interaction with the working parts of the baking powder [6]. There are also attempts to describe the process with empirical formulas based on experimental material [7]. Even though the models sufficiently solve the problems assigned to them, due to the assumptions made in the development or analysis of the models, some questions were not answered, which led to the development of a dynamic model that takes into account the masses of the speck associated with the fibrous material by an elastic band, the force of dry friction interacting with the surface of the material.

Let the fibrous mass contain a speck of mass m_c , which is connected to it by an elastic element and the force of dry friction. Depending on its location in the fibrous mass, we divide the mote into two types. The first type of specks is located on the surface of the scrap and in contact with the mesh surface. Such specks have an angular velocity equal to the speed of the peg, and in addition, under the influence of centrifugal force, they predominantly move through the mesh hole in the radial direction from the center. We denote the distance from the center to the speck by $r(t)$. We assume that the speck is connected to the fibrous mass through an elastic element with variable stiffness and write the equation of motion of the speck

$$m_c \ddot{r} = m_c g \sin(\alpha + \omega t) + m_c \dot{r}^2 / R - k_c (r - R) \quad (1)$$

where k is the stiffness coefficient of the mote-fiber bundle and depends on the movement $r - R$, i.e. $k_c = k_c(r - R)$, where the function $k_c(z)$ is determined experimentally and has a monotonically decreasing character, and after the separation of the speck from the fibrous mass it becomes zero, i.e. should be taken $k_c(z) = 0$ at $z > z_0$. In particular, this function can be chosen as piecewise constant $k = k_0$ for $z < z_0$ and $k = 0$ for $z > z_0$ or piecewise linear $k_c = k_1(z_0 - z)$ for $z \leq z_0$ and $k = 0$ for $z \geq z_0$.

The displacement $r(t)$ satisfies the following initial conditions

$$r = R, \quad \dot{r} = R\omega_0^2 \text{ at } t = 0$$

In this case, the time for $t = t_k$ a speck to leave the mesh surface is determined from equations:

$$k[r(t_k) - R] = 0$$

If $t_0 \leq t_k$ then the speck manages to leave the surface of the mesh during the contact of the scrap with the surface of the mesh, $t_0 > t_k$ then the speck after the interaction of the scrap with the mesh surface does not leave the scrap and continues to move with it. The results of integration of equation (1) are presented in (Fig. 1)

The second type includes specks that are found in the fibrous mass at a distance r_1 from the center of the drum, and $r_1 < R$.

In this case, these types of specks move for some time in the area inside the fibrous mass, and the movement of the specks relative to the shred is predominantly in the radial direction.

To compile the equation of motion of a mote, we assume that the mote is acted upon by the force of connection between the mote and the fibers, as well as the frictional force on the surface of their contact as a result of the movement of the mote relative to the fibrous mass. We assume that the friction force

is directed tangentially to the trajectory of the mote, and the mote makes an angular movement together with the piece of fibrous mass.

We set the origin of the coordinate in the center of the drum and determine the position of the speck by coordinates (x, y) in the plane xOy .

$$x = r(t)\sin\theta, \quad y = r(t)\cos\theta \quad (2)$$

Let's create equations for the kinetic energy of a speck

$$T = \frac{m_c}{2}(\dot{x}^2 + \dot{y}^2) = \frac{m_c}{2}(\dot{r}^2 + r^2\dot{\theta}^2) \quad (3)$$

The following forces act on the mote with projections along the axes Ox and Oy

1. Gravity of a speck

$$X_1 = 0, \quad Y_1 = -m_c g \quad (4)$$

2. The strength of the binding of the mote to the fibers, depending on the distance

$$r - R$$

$$X_2 = -k_c(r - R)(r - R)\sin\theta, \quad Y_2 = -k_c(r - R)(r - R)\cos\theta \quad (5)$$

3. Dry friction force on the contact surface of the speck with the fibrous mass

$$X_3 = -mgf \frac{\dot{x}}{\sqrt{\dot{r}^2 + r^2\dot{\theta}^2}}, \quad Y_3 = -mgf \frac{\dot{y}}{\sqrt{\dot{r}^2 + r^2\dot{\theta}^2}} \quad (6)$$

We accept the coordinate r as a generalized one and find the generalized force

$$Q_r = (X_1 + X_2 + X_3) \frac{\partial x}{\partial r} + (Y_1 + Y_2 + Y_3) \frac{\partial y}{\partial r}$$

Using expressions (3.12.4) - (3.12.6), we obtain

$$Q_r = -k_c(r - R)(r - R) - \frac{mgf\dot{r}}{\sqrt{\dot{r}^2 + r^2\dot{\theta}^2}} - mg \cos\theta \quad (7)$$

Let us now compose the Lagrange equation of the second kind

$$\frac{d}{dt} \left(\frac{\partial T}{\partial \dot{r}} \right) - \frac{\partial T}{\partial r} = Q_r$$

Putting expressions for kinetic energy (3) and generalized force (7), we compose an equation to determine the variable r

$$m_c \ddot{r} = m_c \dot{\theta}^2 r^2 - k_c(r - R)(r - R) - \frac{m_c g f \dot{r}}{\sqrt{\dot{r}^2 + r^2 \dot{\theta}^2}} + m_c g \sin\theta \quad (8)$$

Equation (8) for a known angular displacement of the scrap $\theta = \theta(t)$

integrates under initial conditions $r = R, \dot{r} = R\omega_0$ at $t = 0$

From the results, it is clear that this parameter plays a significant role in the process of removing the speck. At small values, the speck is quickly removed from the composition of the scrap. For example, if we assume that the separation of the speck

from the scrap occurs when the stretching value is reached $\delta = 0.02$, then the weight of the speck for which the parameter ω_{**} takes values $\omega_{**} < 1000$, then they are removed from the fibrous mass. The remaining specks are where $\omega_{**} > 1000$, then the initial speed of the speck will be insufficient for them to be removed from the mass. If the drum speed is accepted, $\omega_{\delta} = 120 \text{ cec}^{-1}$ then specks with the parameter $\omega_{**} = 1000$ will also be removed.

Similar mathematical models have been compiled and used in other cotton processing processes when dismantling the reel and supplying cotton for processing, ginning cotton, and during pneumatic transportation of fibrous material [8] – [18].

Conclusions. As a result of the analysis of the dynamic model of the interaction of trash impurities with the fibrous mass in the presence of an elastic connection between them, the dependence of the parameters of the movement of trash on the angular velocity and radius of the working drum of the cleaner was established, which can be used in the development of cleaners for raw cotton.

REFERENCES

- [1] Handbook of primary processing of cotton. Edited by Omonov and F.B. (in Uzbek). Tashkent-2008
- [2] Miroshnichenko G.I. _ Fundamentals of designing machines for primary processing of cotton. – M., “Mechanical Engineering”, 1972. – 486 p.
- [3] Lebedev D.A. and etc . A nonlinear model of the impact on a weed particle during fiber cleaning. Journal "Textile Industry Technology", No. 5(320), 2009.
- [4] Korabelnikov A.R. etc. Isolation of impurities from the surface of a layer of fibrous material. Journal "Textile Industry Technology", No. 4(340), 2012.
- [5] Korabelnikov A.R., Korabelnikov R.V., Lebedev D.A. Theoretical aspects of the mechanism of release of weed particles from fibrous material when layers are shifted (discharge). Journal "Textile Industry Technology", No. 8(329), 2010.
- [6] Khosrovyan I.G. and others. The general theory of the dynamics of fibrous complexes in the process of their interaction with the working bodies of the baking powder. Journal "Textile Industry Technology", No. 6(342), 2012.
- [7] Sevostyanov A.G. Methods and means for studying mechanical and technological processes in the textile industry. Moscow » Easy industry ". 1980.
- [8] Mardanov B., Sarimsakov O., Theoretical study of the process of mechanical breakdown of cotton seeds. // J ournale of F e r gana P olitechnial Insitute . 2017, No. 1, B.125-127
- [9] Abbazov I., O. Sarimsakov, M. Khodjiev, B. Mardonov. Waste Produced at Cotton Waste Factories. // American Jural ASCIT Communications. 2018; 5(2): pp.22-28
- [10] Sarimsakov O. Ruzmetov M. Dynamics of the interaction of the worker organs with cotton in the bulletproof machine //J.Total problems. 2016, No. 4 , pp.31-34

- [11]Abdukarimovich, MO, Ibragimovich, AK and Sharipjanovich, SO (2018) Designing a New Design of a Loading Cylinder for Pneumomechanical Spinning Machines. Engineering, 10, pp. 345-356.
- [12]Muradov R., Burnashev RZ, Sarimsakov O.Sh. The dynamic task of the interaction of raw cotton with the working bodies of processing machines. // J. Mechanic problems. 2001, No. 34, p. 55-58.
- [13]Obidov A., Akhmedkhodjaev Kh., Sarimsakov O., Holikov Q. Investigation of the Properties of Fibrous Cotton Seeds, for Sorting on a Mesh Surface. // Scientific Research Publishing. The USA. J.Engineering. 2018,10, pp.572-578.
- [14]Sarimsakov O. The possibility of reducing cotton consumption in cotton. // American Journal of Science and Technology. // 2016; 4 (6): pp.68-72. <http://www.aascitjournal.com/ajst>.
- [15]Sarimsakov O., Isaev Sh., Sultanov O., Goybnazarov E. Theoretical Features of the Process Cleaning Zone between Sections of Raw Cotton from Weed Impurities // Engineering, 2020, 12, 739-747 (Web of Science), <https://www.scirp.org/journal/eng>
- [16]Sarimsakov O., Sh. Ergashev, K.Sharipov, Improvement of the Process of Separation of Cotton Fiber from Seeds // [Engineering > Vol.14 No.12, December 2022](#) // Engineering, 14, 567-577. doi: [10.4236/eng.2022.1412042](https://doi.org/10.4236/eng.2022.1412042)
- [17]Sarimsakov O., Sharibaev, E., Sharifbaev, R. Process monitoring of devil machine electric engine in cotton primary processing enterprises // AIP Conference Proceedings this link is disabled, 2023, 2700, 050024
- [18]Sarimsakov O., Sultanov, S., Makhkamov, A. Modeling the process of air separation of cotton particles in roll box of the seed-cotton separators // AIP Conference Proceedings this link is disabled, 2023, 2700, 070011
- [19]Sharipjanovich, S. O. Yo'ldashev Xasanboy Sulaymon O'gli. Sharipov Xayrullo Numonjonovich, Madumarov Sanjarbek Rustamjonovich, INVESTIGATION OF SEPARATION OF USABLE FIBERS ADDED TO CONTAMINANTS DURING CLEANING COTTON "O 'ZBEKISTONDA FANLARARO INNOVATSIYALAR VA ILMIY TADQIQOTLAR" JURNALI.
- [20]Sharifjanovich, S. O., & Khamidovich, K. A. M. (2023). Increasing the efficiency of fiber cleaning by improving the process of removing cotton fiber from the teeth of the saw. Multidisciplinary Journal of Science and Technology, 3(5), 346-349.
- [21]Xasanboy, Y., & Azamjon, D. Theoretical Analysis of storing, cleaning, and processing of seed cotton. Scientific Journal Impact Factor.
- [22]Йўлдашев, Х. С., Инамова, М. Д., Саримсаков, О. Ш (2023) АРРАТИШЛАРИДАН ПАХТА ТОЛАСИНИ ЕЧИБ ОЛИШ ЖАРАЁНИ ПАРАМЕТРЛАРИНИ ИЛМИЙ АСОСЛАШ. "ILM-FAN VA INNOVATION RIVOJLANISH" xalqaro ilmiy-texnikaviy jurnal, 6(6) 84-95
- [23]Numonjonovich, S. X., Rustamjonovich, M. S., & Sharipjanovich, S. O. (2022). INVESTIGATION OF SEPARATION OF USABLE FIBERS ADDED TO CONTAMINANTS DURING CLEANING COTTON. O'ZBEKISTONDA

FANLARARO INNOVATSIYALAR VA ILMIY TADQIQOTLAR
JURNALI, 1(8), 488-493.

- [24] Abdulkarimovich, Najmitdinov Shuxrat, and Yuldashev Khasanboy Sulayman o'g'li. "Тола ажратиш жараёнида хомашё валиги зичлиги ва тезлигининг ахамияти ўрганиш ва таққослаш." TECHNICAL SCIENCE RESEARCH IN UZBEKISTAN 1.5 (2023): 250-256.
- [25] Jurayev, Y., Yuldashev, K., & Tuhktaev, S. (2022). Investigation of fiber loss in impurities from the ss-15a separator. Евразийский журнал академических исследований, 2(11), 425-431.
- [26] Sarimsakov, O., Yuldashev, K., Tuxtaev, S., Urinboyev, B., & Xoshimov, U. (2023, June). Methodology for performing aerodynamic measurements in cleaning seed cotton. In AIP Conference Proceedings (Vol. 2789, No. 1). AIP Publishing.
- [27] Ibrohim, M., & Xasanboy, Y. (2021). Theoretical analysis of the motion of raw cotton with uniform feeder in a cotton cleaner. The American Journal of Engineering and Technology, 3(01), 13-20.
- [28] Yuldashev, K. S., Abduraximov, K. A., Inamova, M. D., & Mirgulshanov, K. A. (2021). DEVELOPMENT OF THE DESIGN OF A FEEDER OF VIBRATION ACTION FOR SUPPLYING COTTON SEEDS TO LINTER MACHINES. SCIENCE, EDUCATION, INNOVATION IN THE MODERN WORLD, USA.
- [29] Sharipjanovich, S. O., & Maripjanovich, K. D. Yo'ldashev Xasanboy Sulaymon O'gli, Jurayev Yo'ldashxon Yunusxon O'g'li, INVESTIGATION OF LOSING FIBER DURING CLEANING COTTON.«Zamonaviy dunyoda amaliy fanlar: muammolar va yechimlar» nomli ilmiy, masofaviy, onlayn konferensiya, May 18, 2022.
- [30] Нажмитдинов С. и Абдулхафизов Б. (2023). ЭКСПЕРИМЕНТАЛЬНЫЕ ИССЛЕДОВАНИЯ ВАРИАНТОВ ПРОФИЛЕЙ КОЛОСНИКОВЫХ РЕШЕТОК НА ЭКСПЕРИМЕНТАЛЬНОЙ УСТАНОВКЕ МОДУЛЯ КРУПНОГО СОРА. НАУКА И ИННОВАЦИОННОЕ РАЗВИТИЕ , 6 (3), 99-105.
- [31] Sarimsaqov, O., Obilov, B., Isayev, S., Muhsinov, I., Muhiddinov, S., & Inamova, M. (2023, June). Theoretical study of the process of contaminants from raw cotton moving on the surface of the grate. In AIP Conference Proceedings (Vol. 2789, No. 1). AIP Publishing.
- [32] Muhsinov, I., Sarimsaqov, O., & Egamov, S. Mexanik yuklanish ta'sirida tebranuvchi to'rli yuzadagi kichik tebranishlarining tahlili. In The X International Scientific and Practical Conference" Trends and prospects for the development of modern education", November 20-22, 2023, Munich, Germany. 422p. (p. 361).
- [33] Isaev, S., Inamova, M., & Muxsinov, I. (2023). Paxta Chigitini Laboratoriya Sharoitida Analizlar Taxlili. Talqin va tadqiqotlar, 1(21).
- [34] Sarimsakov, I Muhsinov "Theoretical Study of the Movement of a Piece of Cotton on the Surface of the Grid in the Process of Separating Large Impurities from Raw

Cotton” International Journal of Innovative Research in Sciences and Engineering Studies (IJIRSES) www.ijirses.com ISSN: 2583-1658 | Volume: 2 Issue

- [35]Нажмитдинов, Ш. А., Шарипов Х. Н. (2023). Совершенствование процесса отделения хлопкового сырья от несущего воздуха ресурсосберегающим способом. Республиканская научно-практическая конференция «XXI АСРДА ИННОВАЦИОННЫХ ТЕХНОЛОГИЙ, РАЗВИТИЯ НАУКИ И ПЕДАГОГА ДОЛЗАРБ МУАММОЛАР» , 1 (10), 110-117.
- [36]Нажмитдинов, Ш. А., & Шарипов, Х. Н. (2023). Жин машинаси ишчи камерасининг конструкцияси ва бошқа деталларининг тола ажралиш жараёнига таъсир омилларини тадқиқ қилиш. " XXI ASRDA INNOVATION TECHNOLOGIYALAR, FAN VA TA'LIM TARAQQIYOTIDAGI DOLZARB MUAMMOLAR" nomli respublika ilmiy-amaliy konferensiyasi, 1(10), 104-109.
- [37]Тўхтаев Шерзод, & Саримсақов Олимжон (2021). ПАХТА ҒАРАМИНИ МЕХАНИК БУЗИШ ВА ҲАВО ТРАНСПОРТИГА УЗАТИШДАГИ НОТЕКИСЛИКНИ ЎРГАНИШ. Oriental Renaissance: Innovative, educational, natural and social sciences, 1 (4), 477-482.
- [38]Шарипов, К., Ахметходжаев, К., и Мардонов, Б. (2019). Теоретические исследования движения одной опоры вдоль колосниковых решеток с конечным профилем джина. Проблемы механики, 4, 55-58.
- [39]Шарипов К., Ахметходжаев К., Таджибаев М., Саримсақов О. Математическая модель движения семян по вогнутому профильному ребру. Машиностроение, 2020, 12, 216-227.
- [40]Azimov SS, Tursunov IT, Yuldashev KS. DEVELOPMENT OF THE DESIGN OF A FEEDER OF VIBRATION ACTION FOR SUPPLYING COTTON SEEDS TO LINTER MACHINES Proceeding IX International Conference «Industrial Technologies and Engineering» ICITE–2022, Volume IV M. Auezov South Kazakhstan University, Shymkent, Kazakhstan December. 2022:09-10.